PFEIFFER VACUUM

Hakuto 伯東



HiPace® 80


Compact yet powerful turbopumps with pumping speeds of up to 71 l/s for N_2




Similar Image

HiPace® 80 with TC 110, E74 and power supply OPS 70, DN 63 CF-F

- Small yet powerful turbopump with a pumping speed of up to 67 l/s for N_2
- Integrated drive electronics TC 110 and interface E74 and power supply OPS
- For installation in any orientation
- Ideal for dependable systems integration
- Extensive accessories expand the range of applications



Dimensions



Technical Data	HiPace® 80 with TC 110, E74 and power supply OPS 70, DN 63 CF-F
Bearing	Hybrid
Compression ratio for Ar	> $1 \cdot 10^{11}$
Compression ratio for H_2	$1.4 \cdot 10^5$
Compression ratio for He	$1.3 \cdot 10^7$
Compression ratio for N_2	> $1 \cdot 10^{11}$
Cooling method, optional	Air
Cooling method, standard	Convection
Electronic drive unit	with TC 110
Flange (in)	DN 63 CF-F

Technical Data	HiPace® 80 with TC 110, E74 and power supply OPS 70, DN 63 CF-F
Flange (out)	DN 16 ISO-KF / G 1/4"
Fore-vacuum max. for N_2	19 hPa | 14.25 Torr | 19 mbar
Gas throughput at full rotational speed for Ar	0.37 hPa l/s | 0.28 Torr l/s | 0.37 mbar l/s
Gas throughput at full rotational speed for H_2	8.9 hPa l/s | 6.67 Torr l/s | 8.9 mbar l/s
Gas throughput at full rotational speed for He	2.3 hPa l/s | 1.73 Torr l/s | 2.3 mbar l/s
Gas throughput at full rotational speed for N_2	0.7 hPa l/s | 0.53 Torr l/s | 0.7 mbar l/s
Integrated power supply	yes
Interface, extended	E74
Interfaces	RS-485, Remote, E74
Mounting orientation	in any orientation
Operating voltage	24 (± 5 %) V DC
Permissible magnetic field max.	3.3 mT
Protection category	IP 30
Pumping speed for Ar	66 l/s
Pumping speed for H_2	48 l/s
Pumping speed for He	58 l/s
Pumping speed for N_2	67 l/s
Rotation speed ± 2 %	90,000 min^{-1}
Rotation speed variable	50-100 %
Run-up time	1.9 min
Sound pressure level	48 dB (A)
Ultimate pressure according to PNEUROP	< 1 · 10^{-8} hPa | < 7.5 · 10^{-9} Torr | < 1 · 10^{-8} mbar
Venting connection	G 1/8"
Weight	4.4 kg | 9.7 lb

Order number	
HiPace® 80	**PM P04 394**

Accessories	
Accessory for TC 110	
Mains power plug angled for TC 110/120 and mating plug for interface E74	**P 4723 111**
Mains power plug for TC 110/120 and mating plug for E74 interface, straight	**P 4723 110**
TCS 11, adapter for TC 110/120 with RS-485 interface	**PM 061 636 -U**
TCS 12, adapter for TC 110/120 with interface RS-485, 4 accessory ports and coupling set	**PM 061 638 -U**
TCS 13, adapter for TC 110/120 with interface RS-485, 2 accessory ports and coupling set	**PM 061 856 -U**
Adapter and control cables	
Control cable for valve	**PM 061 687 -T**
HiPace - ACP connection cable	**PM 071 142 -X**
Air cooling	
Air cooling for HiPace 60/80, SplitFlow 50/80, 230 V	**PM Z01 343**
Air cooling for HiPace 60 P, HiPace 80 and SplitFlow 50/80 with TC 110/120	**PM Z01 300**
Air cooling for HiPace 60 P and 80, SplitFlow 50/80, 115 V	**PM Z01 344**
CF-F, Mounting kit	
Set of hexagon screws for trough hole, DN 63 CF-F	**PM 016 683 -T**
Set of stud screws for tapped hole, 8 count M8, DN 63 CF-F	**PM 016 684 -T**
Set of stud screws for trough hole, DN 63 CF-F	**PM 016 733 -T**
CF-F, Sealings, splinter shields, protection screens	
Protection screen for DN 63 CF-F	**PM 016 333**
Splinter shield for turbopumps, DN 63 CF-F	**PM 016 312**
Control and display units	
Accessories package for HPU 001/PC	**PM 061 005 -T**
DCU 002, Display Control Unit	**PM 061 348 -T**
HPU 001, Handheld Programming Unit	**PM 051 510 -T**
RJ 45 interface cable on M12 for HiPace	**PM 051 726 -T**
Fore-vacuum safety valves	
TVV 001 fore-vacuum safety valve, 115 V AC	**PM Z01 206**
TVV 001 fore-vacuum safety valve, 230 V AC	**PM Z01 205**
Interface and extension cables	
Interface cable, M12 m straight/ M12 m angled 0.7 m	**PM 061 791 -T**
Interface cable, M12 m straight / M12 m straight, 3 m	**PM 061 283 -T**
Mains cables	
Mains cable 115 V AC, NEMA 5-15 to C13, 3 m	**P 4564 309 ZE**
Mains cable 208 V AC, NEMA 6-15 to C13, 3 m	**P 4564 309 ZF**
Mains cable 230 V AC, CEE 7/7 to C13, 3 m	**P 4564 309 ZA**
Power failure venting units (normally open)	
Schielded power failure venting unit, 24 V DC, G 1/8", for connection to TC 110/120	**PM Z01 330**
Relay boxes	
Relay box, shielded, for backing pumps, 1-phase 7A for TC 110/120 and TCP 350, plug M8	**PM 071 282 -X**
Relay box for backing pump, single phase 20 A for TC 110/120 and TCP 350, M8 plug	**PM 061 373 -T**

Accessories	
RS-485	
Connector M12 to RS-485	**PM 061 270 -X**
Power separator for RS-485	**PT 348 132 -T**
Termination resistor for RS-485	**PT 348 105 -T**
USB converter to RS-485 interface	**PM 061 207 -T**
Y-Connector M12 to RS-485	**P 4723 010**
Sealing gas	
Sealing gas throttle for HiPace 60/80	**PM Z01 316**
Sealing gas valve, shielded for HiPace 60/80 with TC 110	**PM Z01 310**
TPS-19" rack module	
Front panel kit for TPS 111	**PM 061 393 -T**
Venting accessory with small flange, G 1/8", hoses, air drier	
Banjo fitting	**PM 016 787 -T**
Banjo fitting, small	**PM 143 877 -T**
Hose nozzle for 9 mm hose, G 1/8"	**PM 016 783 -T**
Plug-in fitting for 6 mm hose, G 1/8"	**PM 016 781 -T**
Plug-in fitting for 8 mm hose, G 1/8"	**PM 016 782 -T**
Screw-in flange, DN 10 ISO-KF, G 1/8"	**PM 033 737 -T**
Screw-on flange, DN 16 ISO-KF, G 1/8"	**PM 016 780 -T**
TTV 001, dryer for venting turbopumps	**PM Z00 121**
Venting valve (normally closed)	
Venting valve, 24 V DC, G 1/8" without cable	**PM Z01 293**
Venting valve, shielded, 24 V DC, G 1/8", for connection to TC 110/120	**PM Z01 290**
Vibration damper	
Vibration damper for HiPace 60/80, DN 63 CF-F	**PM 006 801 -X**